

Maschinenschrauben Linsenkopf

Kreuzschlitz PH DIN 7985

4.8 verzinkt

Größe	Steigung	Bit	Kopfhöhe	Kopfdurchmesser	Kernlochbohrer	Durchgangsloch (mittel)	Längen
M2	0,4				1,6	2,4	4, 5, 6, 8, 10, 12, 16
M2,5	0,45				2,05	2,9	5, 6, 8, 10, 12, 14, 16, 20, 25
M3	0,5				2,5	3,4	4, 8, 10, 12, 14, 16, 18, 20, 22, 25, 28, 30
M3,5	0,6	PH2	2,7	7	2,9	3,9	6, 8, 25
M4	0,7				3,3	4,5	4, 5, 6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 28, 30, 35, 40, 45, 50, 55, 60
M5	0,8				4,2	5,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 70
M6	1				5	6,6	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70
M8	1,25				6,8	9	10, 12, 16, 18, 20, 25, 30, 35, 40, 45, 50, 60, 70

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.