53-A Stud extractor set for tight spaces Ø 6, 8, 10, 12 mm





DETAIL IMAGE



DESCRIPTION

The stud extractor set of series 53 is used for extracting stud bolts or broken components in automotive and industry applications. Kukko stud extractors are available in various diameters and designs. The series 53 can also be used in the tightest spaces due to its design and is operated with a ring or socket wrench. The set includes 4 different extractors with various diameters from 6 – 12 mm.

APPLICATION AREA

To remove stud bolts or broken components in automotive and industry.

BENEFIT

- Application-oriented assembly for universal use
- The knurled wheel with a groove securely presses the stud bolt against the internal toothing.
- During extraction, the stud bolt is located in the area of the key and cannot break.

OPERATION

- Position the stud extractor on the stud bolt
- Drive the extractor using a ring or socket wrench and securely extract the stud bolt

MASTER DATA

GTIN [GTIN]	4021176222801
Country of origin	DE
Material	Tool steel
Series	53-A
Gross weight [kg]	0,715 kg
Package contents	1 piece
Packaging Act	PAP 20
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 53-10_Stud Extractor for Tight Spaces
- 53-12_Stud Extractor for Tight Spaces
- 53-6_Stud Extractor for Tight Spaces
- 53-8_Stud Extractor for Tight Spaces