

Zeskantbouten DIN 931

RVS A2

Maat	Spoed	Sleutelwijdte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M5	0,8	8	4,2	5,5	40, 45, 50, 60, 70, 80
M6	1	10	5	6,6	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 120
M8	1,25	13	6,8	9	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150
M10	1,5	17	8,5	11	45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150
M12	1,75	19	10,2	13,5	45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150
M14	2	22	12	15,5	70, 75, 80, 90, 100, 110, 120, 130, 140, 150
M16	2	24	14	17,5	60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M18	2,5	27	15,5	20	80, 90, 100, 110, 120, 130, 140, 150
M20	2,5	30	17,5	22	65, 70, 80, 90, 100, 110, 120, 130, 140, 150
M22	2,5	32	19,5	24	90, 100, 110, 120, 130, 140, 150
M24	3	36	21	26	100, 110, 120, 130, 140, 150, 160, 170, 180

Maten in mm. Nominale maten; de toleranties staan in de norm.