DIN 7983 similar to ISO 7051


Tapping screws

Raised countersunk head | cross-slot phillips | form C with cone point



Steel | zinc-plated | Cr(VI)-free | Thread type ST (sheet metal)

Further information: DIN-standard has been withdrawn | changed head measurements



Diameter (d)	Tool size	a max.	d_k min.	d_k max.	f	k	rf	r max.	Pitch (P)
2.2	H1	0.8	4.00	4.3	0.7	1.3	3.8	0.8	0.8
2.9	H1	1.1	5.20	5.5	0.9	1.7	4.6	1.1	1.1
3.5	H2	1.3	6.44	6.8	1.2	2.1	5.4	1.4	1.3
3.9	H2	1.3	7.14	7.5	1.3	2.3	6.0	1.5	1.3
4.2	H2	1.4	7.74	8.1	1.4	2.5	6.6	1.6	1.4
4.8	H2	1.6	9.14	9.5	1.5	3.0	8.2	1.9	1.6
5.5	H3	1.8	10.37	10.8	1.7	3.4	9.4	2.1	1.8
6.3	H3	1.8	11.97	12.4	2.0	3.8	11.1	2.4	1.8

Length (l)		
nominal size	min.	max.
9.5	8.7	10.3
13.0	12.2	13.8
16.0	15.2	16.8
19.0	18.2	19.8
22.0	21.2	22.8
25.0	24.2	25.8

Length (l)		
nominal size	min.	max.
32.0	31.2	33.3
38.0	37.2	39.3

All technical data refer to the measure mm

All technical data without obligation. Subject to technical changes and errors.

DIN 7983 similar to ISO 7051

Tapping screws

Raised countersunk head | cross-slot phillips | form C with cone point

Steel | zinc-plated | Cr(VI)-free | Thread type ST (sheet metal)

Diameter	Length (l)							
(d)	9.5	13	16	19	22	25	32	38
2.2	●							
2.9	●	●	●					
3.5		●	●	●				
3.9		●	●	●		●		
4.2		●	●	●	●	●		
4.8			●	●		●	●	
5.5						●		●
6.3						●		

All technical data refer to the measure mm

All technical data without obligation. Subject to technical changes and errors.