

Zylinderschrauben mit Innensechskant DIN 912

10.9 blank

Größe	Steigung	Innensechskant	Kopfhöhe	Kopfdurchmesser	Kernlochbohrer	Durchgangsloch	Längen
						(mittel)	
M3	0,5	2,5	3	5,5	2,5	3,4	6, 8, 10, 12, 16, 20, 25
M4	0,7	3	4	7	3,3	4,5	6, 8, 10, 12, 16, 20, 25, 30
M5	0,8	4	5	8,5	4,2	5,5	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 85, 90, 100, 150
M6	1	5	6	10	5	6,6	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120
M8	1,25	6	8	13	6,8	9	12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130
M10	1,5	8	10	16	8,5	11	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 125, 130, 140, 150, 160, 170
M12	1,75	10	12	18	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 125, 130, 140, 150, 160, 170, 180
M14	2	12	14	21	12	15,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 125, 130, 140, 150
M16	2	14	16	24	14	17,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M18	2,5	14	18	27	15,5	20	50, 55, 60, 70, 75, 80, 90, 100, 110

Größe	Steigung	Innensechskant	Kopfhöhe	Kopfdurchmesser	Kernlochbohrer	Durchgangsloch	
						(mittel)	Längen
M20	2,5	17	20	30	17,5	22	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180, 190, 200, 210, 220
M24	3	19	24	36	21	26	50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 200, 220

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.