43-11 3-jaw small parts puller with force-amplifying, self-centering jaws, up to 60 mm spread, 50 mm reach



DESCRIPTION

The handy 3-jaw small parts puller with force-amplifying and self-centering jaws is used for sensitive Pulling of small bearings, gears and washers in tight, hard-to-reach gaps. The compact and space-saving design of the puller with slender jaws that become wider towards the claw is particularly suitable for electric motors. The freely movable pin on the T-handle guarantees comfortable one-handed tightening of the spindle in the tightest spaces.

APPLICATION AREA

For the sensitive removal of small bearings, gears, and discs in tight, hard-to-access spaces.

BENEFIT

- Self-centering of the jaws through manual tightening of the spindle (Autogrip Technology)
- Integrated, free-moving pen on the T-handle guarantees manual spindle drive in tight spaces
- The slim design of the jaws allows access to hard-to-reach places.
- No additional tool is required for the pulling process.

OPERATION

- Position the puller jaws from the outside onto the part to be pulled off
- Swing the claws under the component
- Manually pull the spindle for fixation
- Set the T-handle at the spindle head in motion until the component is loosened


MASTER DATA


GTIN [GTIN]	4021176015526
Country of origin	DE
Material	Tool steel
Series	43-10
Gross weight [kg]	0,275 kg
Package contents	1 piece
Packaging Act	Rezykkat rHDPE 61
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 43-1-206_Press spindle
- 43-11-50-S_3 puller (set)
- 43-11-T_Crossbar


3-jaw small parts puller with force-amplifying, self-centering jaws, up to 60 mm spread, 50 mm reach






Abbreviation	Attribut	Wert
X	Total width [mm]	78 mm
Y	Total depth [mm]	78 mm
Z	Total height [mm]	107 mm
A	Clamping depth of external puller [mm]	50 mm
Cmin	Span outside pull-off (min.) [mm]	0 mm
Cmax	Span outside pull-off (max.) [mm]	60 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	2 mm
J	Hook base width (claw width J) [mm]	11 mm
O	Hook base depth usable (claw depth usable O) [mm]	10 mm
H	Total hook root depth (total claw depth H) [mm]	19 mm
L	Total claw thickness (L+1mm) [mm]: (claw distance to base surface)	5 mm
Fmax	Max. tractive force [t]	1.5 t
Fmax	Max. tensile force [kN]	15 kN

Abbreviation	Attribut	Wert
X	Total width [mm]	78 mm
Y	Total depth [mm]	78 mm
Z	Total height [mm]	107 mm
A	Clamping depth of external puller [mm]	50 mm
Cmin	Span outside pull-off (min.) [mm]	0 mm
Cmax	Span outside pull-off (max.) [mm]	60 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	2 mm
J	Hook base width (claw width J) [mm]	11 mm
O	Hook base depth usable (claw depth usable O) [mm]	10 mm
H	Total hook root depth (total claw depth H) [mm]	19 mm
L	Total claw thickness (L+1mm) [mm]: (claw distance to base surface)	5 mm
Fmax	Max. tractive force [t]	1.5 t
Fmax	Max. tensile force [kN]	15 kN



Abbreviation	Attribut	Wert
X	Total width [mm]	78 mm
Y	Total depth [mm]	78 mm
Z	Total height [mm]	107 mm
A	Clamping depth of external puller [mm]	50 mm
Cmin	Span outside pull-off (min.) [mm]	0 mm
Cmax	Span outside pull-off (max.) [mm]	60 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	2 mm
J	Hook base width (claw width J) [mm]	11 mm
O	Hook base depth usable (claw depth usable O) [mm]	10 mm
H	Total hook root depth (total claw depth H) [mm]	19 mm
L	Total claw thickness (L+1mm) [mm]: (claw distance to base surface)	5 mm



Abbreviation	Attribut	Wert

Fmax	Max. tractive force [t]	1.5 t
Fmax	Max. tensile force [kN]	15 kN

X	Total width [mm]	78 mm
Y	Total depth [mm]	78 mm
Z	Total height [mm]	107 mm
A	Clamping depth of external puller [mm]	50 mm
Cmin	Span outside pull-off (min.) [mm]	0 mm
Cmax	Span outside pull-off (max.) [mm]	60 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	2 mm
J	Hook base width (claw width J) [mm]	11 mm
O	Hook base depth usable (claw depth usable O) [mm]	10 mm
H	Total hook root depth (total claw depth H) [mm]	19 mm
L	Total claw thickness (L+1mm) [mm]: (claw distance to base surface)	5 mm
Fmax	Max. tractive force [t]	1.5 t
Fmax	Max. tensile force [kN]	15 kN