

Sechskantschrauben DIN 933

8.8 blank

Größe	Steigung	Schlüsselweite	Kopfhöhe	Kernlochbohrer	Durchgangsloch (mittel)	Längen
M3	0,5	5,5	2	2,5	3,4	8
M4	0,7	7	2,8	3,3	4,5	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 60
M5	0,8	8	3,5	4,2	5,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 70
M6	1	10	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60
M8	1,25	13	5,3	6,8	9	10, 12, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M10	1,5	17	6,4	8,5	11	12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 120
M12	1,75	19	7,5	10,2	13,5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M14	2	22	8,8	12	15,5	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 100
M16	2	24	10	14	17,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 120
M18	2,5	27	11,5	15,5	20	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M20	2,5	30	12,5	17,5	22	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M22	2,5	32	14	19,5	24	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M24	3	36	15	21	26	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.