129-5 Ball joint press for heavy-duty trucks, with 36 mm jaw opening, 15 t max. tension force



DESCRIPTION

The ball joint press for heavy duty trucks in the series 129-5 is used for pressing out the ball pins during the disassembly of ball joints on drag and tie rods, specifically for medium and heavy-duty trucks, buses, and construction vehicles. The series 129 impresses with its versatility of application. The lever span is adjustable via the thread of the center spindle.

APPLICATION AREA

For pressing out the ball studs during the removal of ball joints on tie rods and drag links, specifically for medium and heavy trucks, buses, and construction vehicles.

BENEFIT

- The bolt can be adjusted to flexibly adapt the clamping range.

OPERATION

- Fastener between ball joint and part
- Spindle torqued with torque wrench
- Threaded pin of the ball joint is pressed out of the component

MASTER DATA

GTIN [GTIN]	4021176865084
Country of origin	DE
Material	Tool steel
Series	129-5
Gross weight [kg]	4,24 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 129506_adjusting screw
- 129514_Body
- 129531_Clamping lever
- 129557_Hinge shaft