K-22-A-E 6-piece ball bearing extractor set Ø 4.8-16 mm



DETAIL IMAGE



DESCRIPTION

The 6-piece ball bearing puller set with counter stay and sliding hammer K-22-A-E is used for extracting flat-mounted bearings, bearing outer rings, and bushings in craftsmanship, workshops, and industry. The segmented design with extra fine gripping edges allows for the secure extraction of flat-mounted parts. The included counter stay or sliding hammer is used in conjunction with the internal extractors depending on whether a sufficient support surface is available.

APPLICATION AREA

For extracting flat bearings, bearing outer rings and bushes

OPERATION

- Determine the inner diameter of the ball bearing and select the appropriate internal puller
- Insert the internal puller into the hole and tighten the locking nut
- If a support surface is available, choose the counter stay; otherwise, select the sliding hammer

Operation with counter stay:

- Support the counter stay on the housing and screw it onto the wedge spindle of the internal puller
- Hold the handle of the counter stay and safely pull out the bearing by tightening the nut
- Retighten the locking nut while pulling out

Operation with sliding hammer:

- Screw the sliding hammer rod onto the wedge spindle of the internal puller
- Use the sliding hammer with a striking motion to pull out the bearing

MASTER DATA

GTIN [GTIN]	4021176140471
Country of origin	DE
Material	Tool steel
Series	K-22-E
Gross weight [kg]	2,8 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 21-0-E_Internal Extractor
- 21-00-E_Internal Extractor
- 21-01-E_Internal Extractor
- 21-1-E_Internal Extractor
- 22-0-05 Sliding Hammer Device with 0.5 kg Impact Weight
- 22-1_Counter Stay
- Powernut