

Socket head cap screws DIN 912

stainless steel A4

Size	Pitch	Hex key	Head height	Head diameter	Tap drill	Clearance hole (medium)	Lengths
M1.4							4
M2	0.4	1.5	2	3.8	1.6	2.4	4, 5, 6
M2.5	0.45	2	2.5	4.5	2.05	2.9	5, 6, 8
M3	0.5	2.5	3	5.5	2.5	3.4	5, 6, 8, 10, 12, 14, 16
M4	0.7	3	4	7	3.3	4.5	6, 8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45
M5	0.8	4	5	8.5	4.2	5.5	6, 8, 10, 12, 14, 16, 20, 22, 25, 30, 35, 40, 45, 50
M6	1	5	6	10	5	6.6	10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55
M8	1.25	6	8	13	6.8	9	12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M10	1.5	8	10	16	8.5	11	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90
M12	1.75	10	12	18	10.2	13.5	20, 25, 30, 35, 40, 45, 50, 60, 70, 80, 100
M16	2	14	16	24	14	17.5	30, 35, 40, 45, 50, 55, 60, 70, 80, 90, 100

Dimensions in mm. Nominal sizes; tolerances are given in the standard.