

Gewindestifte Innensechskant, Kegelstumpf

ISO 4026

45H blank

Größe	Steigung	Innensechskant	Längen
M2	0,4	0,9	2, 3, 4
M2,5	0,45	1,3	3, 4, 5, 6, 8
M3	0,5	1,5	3, 4, 5, 6, 8, 10, 12, 14, 16
M4	0,7	2	3, 4, 5, 6, 8, 10, 12, 16, 20
M5	0,8	2,5	4, 5, 6, 8, 10, 12, 16, 20, 25
M6	1	3	5, 6, 8, 10, 12, 14, 16, 20, 25, 30
M8	1,25	4	6, 8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55
M10	1,5	5	10, 12, 16, 20, 25, 30, 35, 40, 45, 50, 60, 65, 70, 80
M12	1,75	6	10, 12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70
M16	2		16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 90
M20	2,5		20, 25, 30, 35, 40, 45, 50, 60, 70, 80, 90
M24	3		25, 30, 35, 40, 45, 55, 60, 70, 80, 90, 100

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.