

Zeskantbouten DIN 931

8.8 blank

Maat	Spoed	Sleutelwijdte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M5	0,8	8	4,2	5,5	35, 40, 50, 55, 60, 70
M6	1	10	5	6,6	30, 35, 40, 45, 50, 55, 60, 70, 80, 90
M8	1,25	13	6,8	9	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 100, 110, 120, 130, 140, 150, 160, 170
M10	1,5	17	8,5	11	40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110, 120, 130, 140, 150, 160, 170, 180
M12	1,75	19	10,2	13,5	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M14	2	22	12	15,5	50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150
M16	2	24	14	17,5	55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M18	2,5	27	15,5	20	65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M20	2,5	30	17,5	22	65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M22	2,5	32	19,5	24	80, 90, 100, 110, 120, 130, 140, 150, 160, 180
M24	3	36	21	26	75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M27	3	41	24	30	80, 90, 100, 110, 120, 140, 150, 160, 170

Maten in mm. Nominale maten; de toleranties staan in de norm.