

Zeskantbouten DIN 931

8.8 verzinkt

Maat	Spoed	Sleutelwijdte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M5	0,8	8	4,2	5,5	30, 35, 40, 45, 50, 55, 60, 70
M6	1	10	5	6,6	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 95, 100, 110
M8	1,25	13	6,8	9	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170
M10	1,5	17	8,5	11	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M12	1,75	19	10,2	13,5	40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M16	2	24	14	17,5	50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M20	2,5	30	17,5	22	65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M24	3	36	21	26	70, 80, 90, 100, 110, 120, 130, 140, 150, 170, 200, 210

Maten in mm. Nominale maten; de toleranties staan in de norm.