

Inbusbouten met cilinderkop lage kop DIN 7984

8.8 verzinkt

Maat	Spoed	Inbussleutel	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M3	0,5		1,5		2,5	3,4	5, 6, 8, 10, 12, 14, 16, 20
M4	0,7		2,3		3,3	4,5	6, 8, 10, 12, 14, 16, 20, 25, 30, 40
M5	0,8		2,7		4,2	5,5	8, 10, 12, 16, 20, 25, 30
M6	1		3		5	6,6	10, 12, 16, 18, 20, 25, 30, 35, 40, 45, 50, 70
M8	1,25		3,8		6,8	9	12, 16, 18, 20, 25, 30, 35, 40, 45, 50, 60, 70
M10	1,5		4,5		8,5	11	16, 20, 25, 30, 35, 40, 45, 50, 60
M12	1,75	8	7	18	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 60, 70
M16	2	12	9	24	14	17,5	30, 35, 40, 45, 50
M20	2,5	14	11	30	17,5	22	40, 50, 60

Maten in mm. Nominale maten; de toleranties staan in de norm.