

# Metaalschroeven bolcilinderkop kruiskop PH

## DIN 7985

RVS A2

| Maat        | Spoed | Bit | Kophoogte | Kopdiameter | Kernboor voor<br>tapgat | Doorlaatgat<br>(middel) | Lengtes                                                                           |
|-------------|-------|-----|-----------|-------------|-------------------------|-------------------------|-----------------------------------------------------------------------------------|
| <b>M2</b>   | 0,4   | PH1 | 1,6       | 4           | 1,6                     | 2,4                     | 3, 4, 5, 6, 8, 10, 12, 14, 16, 18, 20                                             |
| <b>M2,5</b> | 0,45  | PH1 | 2         | 5           | 2,05                    | 2,9                     | 4, 5, 6, 8, 10, 12, 14, 16, 18, 20, 25                                            |
| <b>M3</b>   | 0,5   |     |           |             | 2,5                     | 3,4                     | 4, 5, 6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 28, 30, 35                            |
| <b>M4</b>   | 0,7   |     |           |             | 3,3                     | 4,5                     | 4, 5, 6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 28, 30, 35,<br>40, 45, 50, 55, 60, 70 |
| <b>M5</b>   | 0,8   |     |           |             | 4,2                     | 5,5                     | 6, 8, 10, 12, 14, 15, 16, 18, 20, 22, 25, 30, 35, 40,<br>45, 50                   |
| <b>M6</b>   | 1     |     |           |             | 5                       | 6,6                     | 8, 9, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45,<br>50                       |

Maten in mm. Nominale maten; de toleranties staan in de norm.