

Tapbouten DIN 933

8.8 verzinkt

Maat	Spoed	Sleutelwijdte	Kophoogte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M3	0,5	5,5	2	2,5	3,4	6, 8, 10, 12, 16
M4	0,7	7	2,8	3,3	4,5	8, 10, 12, 16, 20, 25, 30, 35, 40, 50
M5	0,8	8	3,5	4,2	5,5	8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50
M6	1	10	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M8	1,25	13	5,3	6,8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M10	1,5	17	6,4	8,5	11	12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M12	1,75	19	7,5	10,2	13,5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120
M14	2	22	8,8	12	15,5	25, 40, 45, 50, 60, 70
M16	2	24	10	14	17,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140
M20	2,5	30	12,5	17,5	22	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M24	3	36	15	21	26	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100

Maten in mm. Nominale maten; de toleranties staan in de norm.