129-1-B-1 Ball joint press with extractor lever for cars, light vans, with 31 mm jaw opening, 3 t max. tension force



DESCRIPTION

The Ball joint press with lever ratio from the 129 series is used to press out the ball studs when removing ball joints as well as tie rod ends on tie rods for car and light vans. Thanks to its lever ratio, the Ball joint press can also apply a lot of force where there is hardly any access space. The 129 series impresses with its wide range of applications. Within the series, there are various sizes of Ball joint press with different jaw opening. The lever clamping range can be adjusted via the thread of the center spindle.

APPLICATION AREA

For pressing out the ball studs when removing Ball joints as well as tie rod ends on tie rods for cars and light delivery vans.

BENEFIT

- The bolt can be adjusted to flexibly adapt the clamping range.

OPERATION

- Attach press between ball joint and component
- Tighten spindle with torque wrench
- Thread pin of the ball joint is pressed out of the component

APPLICATION IMAGE



MASTER DATA

GTIN [GTIN]	4021176923654
Country of origin	DE
Material	Tool steel
Series	129-1
Gross weight [kg]	0,725 kg
Package contents	1 piece
Packaging Act	Rezykkat rHDPE 61
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)