128-50-H Hydraulic ball joint puller, with Ø 46 mm jaw opening, 15 t max. tension force, 85 mm deployment depth



DESCRIPTION

The bell-shaped hydraulic ball joint puller from series 128-H is used for pressing out ball pins when removing ball joints and tie rod ends on tie rods in automotive and industry applications. The puller allows for non-damaging work and is optimal when there is plenty of space available. The 128 series impresses with its fast and easy operation and is available in various sizes. The grease hydraulic spindle achieves an average pulling force of up to 15 t.

APPLICATION AREA

To express the ball pins during the removal of ball joints and tie rod ends on tie rods in automotive and industry.

BENEFIT

- Due to its simple yet effective design, the direct-print ball joint puller is particularly suitable for quick and uncomplicated application.
- The hydraulics ensure a force-saving and safe operation.

OPERATION

- Attach puller between ball joint and component
- Torque the spindle with torque wrench
- Threaded pin of the ball joint is pushed out of the component

MASTER DATA

GTIN [GTIN]	4021176006999
Country of origin	DE
Material	Tool steel
Series	128-H
Gross weight [kg]	4,9 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 801_short hydraulic spindle

APPLICATION IMAGE

