

# Sechskantschrauben DIN 933

10.9 blank

| Größe      | Steigung | Schlüsselweite | Kopfhöhe | Kernlochbohrer | Durchgangsloch<br>(mittel) | Längen                                                              |
|------------|----------|----------------|----------|----------------|----------------------------|---------------------------------------------------------------------|
| <b>M6</b>  | 1        | 10             | 4        | 5              | 6,6                        | 10, 12, 16, 20, 25, 30, 35, 40, 50, 60                              |
| <b>M8</b>  | 1,25     | 13             | 5,3      | 6,8            | 9                          | 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80          |
| <b>M10</b> | 1,5      | 17             | 6,4      | 8,5            | 11                         | 16, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100 |
| <b>M12</b> | 1,75     | 19             | 7,5      | 10,2           | 13,5                       | 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100         |
| <b>M14</b> | 2        | 22             | 8,8      | 12             | 15,5                       | 35, 40                                                              |
| <b>M16</b> | 2        | 24             | 10       | 14             | 17,5                       | 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100         |
| <b>M20</b> | 2,5      | 30             | 12,5     | 17,5           | 22                         | 30, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100                     |
| <b>M24</b> | 3        | 36             | 15       | 21             | 26                         | 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100                         |

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.