

Tapbouten DIN 933

RVS A4

Maat	Spoed	Sleutelwijdte	Kophoogte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M5	0,8	8	3,5	4,2	5,5	12, 16, 20, 25, 30
M6	1	10	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65
M8	1,25	13	5,3	6,8	9	12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M10	1,5	17	6,4	8,5	11	16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M12	1,75	19	7,5	10,2	13,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M14	2	22	8,8	12	15,5	40, 45, 50, 55, 60, 65, 70, 75, 80
M16	2	24	10	14	17,5	25, 30, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 120
M18	2,5	27	11,5	15,5	20	70, 75, 80, 90, 100
M20	2,5	30	12,5	17,5	22	40, 50, 60, 80, 90, 100

Maten in mm. Nominale maten; de toleranties staan in de norm.