

Machine screws cheese head slotted DIN 84

stainless steel A2

Size	Pitch	Head height	Head diameter	Tap drill	Clearance hole (medium)	Lengths
M1		0.7	2			3, 4
M1.2		0.8	2.3			3, 4, 6, 10
M1.4		0.9	2.6			4, 5, 6
M1.6	0.35	1	3	1.25	1.8	6, 8, 10
M2	0.4	1.3	3.8	1.6	2.4	3, 4, 5, 6, 8, 10, 12, 16
M2.5	0.45	1.6	4.5	2.05	2.9	4, 5, 6, 8, 10, 12, 20, 22
M3	0.5			2.5	3.4	5, 6, 8, 10, 12, 16, 20, 25, 35
M4	0.7	2.6	7	3.3	4.5	6, 8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 70
M5	0.8	3.3	8.5	4.2	5.5	6, 8, 10, 12, 16, 20, 25, 30, 40, 45
M6	1	3.9	10	5	6.6	8, 10, 12, 16, 20, 25, 30, 35, 40
M8	1.25	5	13	6.8	9	12, 16, 25, 30, 40
M10	1.5	6	16	8.5	11	16, 35, 45

Dimensions in mm. Nominal sizes; tolerances are given in the standard.