

# Socket head cap screws low head DIN 7984

stainless steel A2

| Size       | Pitch | Head height | Tap drill | Clearance hole (medium) | Lengths                                        |
|------------|-------|-------------|-----------|-------------------------|------------------------------------------------|
| <b>M3</b>  | 0.5   | 1.5         | 2.5       | 3.4                     | 5, 6, 8, 10, 14, 16, 20                        |
| <b>M4</b>  | 0.7   | 2.3         | 3.3       | 4.5                     | 6, 8, 10, 12, 14, 16, 20, 25                   |
| <b>M5</b>  | 0.8   | 2.7         | 4.2       | 5.5                     | 8, 10, 12, 16, 20, 25                          |
| <b>M6</b>  | 1     | 3           | 5         | 6.6                     | 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55 |
| <b>M8</b>  | 1.25  | 3.8         | 6.8       | 9                       | 12, 16, 20, 25, 30, 35, 40, 45, 50, 60         |
| <b>M10</b> | 1.5   | 4.5         | 8.5       | 11                      | 16, 20, 25, 30, 35, 40, 50                     |
| <b>M12</b> | 1.75  | 5           | 10.2      | 13.5                    | 20, 25, 30, 35, 40, 45, 50                     |

Dimensions in mm. Nominal sizes; tolerances are given in the standard.